


# Alcatel-Lucent VPN Firewall Brick 1200 Security Appliance

VPN, VoIP AND QoS SECURITY GATEWAYS



The Alcatel-Lucent VPN Firewall Brick® 1200 security appliances take data security to new levels by providing up to 4.75 Gbps firewall throughput, along with integrated high-speed VPN, VoIP Security, VLAN and virtual firewall capabilities at a break through price. With QoS bandwidth management features, built in IDS/DoS protections and high network performance, the VPN Firewall Brick 1200 security appliances provide solid security for large enterprise, data centers and network-edge environments. This carrier-grade IP services platform provides excellent value with low price/performance and total ownership costs, enabling service providers, government entities and large enterprises to deploy secure IP and VPN services that enhance their business while maximizing returns on their capital investments.



## APPLICATIONS

- Advanced security services
- VPN services for site-to-site and remote access
- Bandwidth management capabilities
- VoIP Security
- Secure data center Web and application hosting
- Storage network security solution
- Mobile data security
- Packet Data Gateway and Packet Data Interworking functions for fixed mobile convergence Wifi VPN and VoIP/data security
- Managed Security Services
- Unlicensed Mobile Access (UMA) and IP Multimedia Subsystem (IMS) Security

## FEATURES

- **Integrated security platform** — Provides high-speed firewall, VPN, QoS, VLAN and virtual firewall capabilities in one configuration
- **Industry-leading throughput** — Delivers up to 4.75Gbps firewall performance, 1.7Gbps 3DES and AES VPN performance with built-in encryption accelerator cards (EAC), depending on the Brick 1200 security appliance version selected.
- **Innovative security services** — Includes advanced distributed denial of service attack protection, latest IKEv2 standards, strong authentication and real-time monitoring, logging and reporting
- **High capacity** — Supports up to 20,000 simultaneous VPN tunnels, 4,094 VLANs, 1100 virtual firewalls, and 3 million simultaneous sessions (HS version)

## BENEFITS

- **Higher performance** — Deliver an enhanced user experience with up to 4.75 Gbps cleartext and 1.7Gbps 3DES and AES IPSec VPN throughput, combined with best-in-class bandwidth management — with customer-level, user-level and server-level QoS control
- **Low price/performance** — Get outstanding security and throughput for less than the per-Mbps price of major competitors
- **Low cost of ownership** — One configuration supports multiple IP services with no additional or recurring licensing fees
- **Flexible deployment** — Options include premises- or network-based services with shared or dedicated hardware environments
- **Economical growth path** — Seamless migration to advanced, VoIP, QoS and VPN security services with no added infrastructure investments

## FEATURES

- **Central staging and secure remote management** — Provides integrated control over thousands of VPN Firewall Brick appliances and IPSec client users (including the Alcatel-Lucent IPSec Client, from one console, using the Alcatel-Lucent Security Management Server (SMS) software
- **High-availability architecture** — Eliminates any single point of failure
- **Proven Secure** — Virtually impenetrable hardened security operating system coupled with secure management infrastructure.

## BENEFITS

- **Economical growth path** — Seamless migration to advanced, VoIP, QoS and VPN security services with no added infrastructure investments
- **Plug-and-play interoperability** — There's no need for costly network reconfigurations or on-site support
- **Cost-effective business continuity** — Take advantage of low priced encryption performance and maintain carrier-class reliability for today's data-heavy business applications
- **Assured business continuity** — native high availability with carrier-class reliability
- **Centralized, scalable, carrier-class management** — Centrally manage up to 20,000 VPN Firewall Brick security appliances and 500,000 Alcatel-Lucent IPSec Client (or third party IPSec client) users with Alcatel-Lucent Security Management Server v9.0 or later.

## TECHNICAL SPECIFICATIONS

### Processor/Memory

- 3.6 GHz Processor with 2GB of RAM for Brick 1200 HS AC and DC models
- 3.2 GHz Processor with 1GB of RAM for Brick 1200 AC Model

### LAN/VPN Interfaces

#### BRICK 1200 HS AC AND DC MODELS

- (14) 10/100/1000 copper ports
- (6) GigE mini-GBIC SFP ports
- (1) VPN Encryption Accelerator

#### BRICK 1200 AC MODEL

- (8) 10/100/1000 copper ports
- (2) GigE mini-GBIC SFP ports
- (1) VPN Encryption Accelerator

### Other Ports

- SVGA video, DB9 serial, PS/2 keyboard, 4xUSB

### Performance

#### BRICK 1200 HS AC OR HS DC

- Concurrent sessions – 3,000,000
- New sessions/second – 45,000
- Rules – 30,000 (shared among all virtual firewalls)
- Maximum cleartext throughput – 4.75Gbps (1460 byte UDP Packets)
- Maximum cleartext PPS throughput – 2,200,000 pps (78 byte UDP Packets)
- Maximum 3DES and AES 256 throughput with hardware encryption acceleration  
→ 1.7 Gbps (1460 byte UDP Packets)

- Maximum 3DES and AES 256 throughput with hardware encryption acceleration  
→ 480,000 pps (78 byte UDP Packets)

#### BRICK 1200 AC

- Concurrent sessions – 2,000,000
- New sessions/second – 30,000
- Rules – 30,000 (shared among all virtual firewalls)
- Maximum cleartext throughput – 4.1 Gbps (1460 byte UDP Packets)
- Maximum cleartext PPS throughput – 2,016,000 pps (78 byte UDP Packets)
- Maximum 3DES and AES 256 throughput with hardware encryption – 1.1 Gbps (1460 byte UDP Packets)
- Maximum 3DES and AES 256 PPS throughput with hardware encryption – 332,000 pps (78 byte UDP Packets)

### Virtualization

- Maximum number of virtual firewalls – 1100 (Brick 1200 HS AC or DC)
- Maximum number of virtual firewalls – 500 (Brick 1200 AC)
- Number of VLANs supported – 4,094
- VLAN domains – up to 16 per VLAN trunk
- VPN Firewall Brick partitions – allows for virtualization of customer IP address range, including support for overlapping IP addresses

### Modes of Operation

- Bridging and/or routing on all interfaces
- All features supported with bridging
- IP routing with static routes
- 802.1Q VLAN tagging supported inbound and outbound on any combination of ports
- Layer-2 VLAN bridging
- Network Address Translation (NAT)
- Port Address Translation (PAT)
- Policy-based NAT and PAT (per rule)
- Supports virtual IP addresses for both address translation and VPN tunnel endpoints
- PPPoE and DHCP-assignable interface/VLAN addresses
- Redundant DHCP Relay capabilities
- Dynamic registration of mobile VPN Firewall Brick security appliance address for centralized remote management
- Nested zone rule sets for common firewall policies for all Bricks in the zone
- Link Aggregation
- Mobile Brick using integrated DHCP Client.

## Services Supported

- Bootp, http, irc, netstat, pop3, SNMP, tftp, pptp, dns, https, kerberos, nntp, rip, ssh, who, RADIUS, eigrp, ident, LDAP, ntp, rip2, syslog, shell, X11, exec, gmp, login, OSPF, rlogin, telnet, talk, H.323, SIP, ftp, imap, mbone, ping, rsh, traceroute, lotus notes, VoIP/SIP, Gopher, IPSec, netbios, pointcast, mtp, sql\*net
- Any IP protocol (user definable)
- Any IP protocol + layer 4 ports (user definable)
- Support for non-IP protocols as defined by SAP/Ethertype

## Layer-7 Application Support

- Application Filter architecture supports layer-7 protocol inspection (deep packet inspection) for command and protocol validation, protocol anomaly detection, dynamic channel pinholes and application layer address translation. Application filters include http, ftp, RPC, tftp, H.323/H.323 RAS, SMTP, Oracle SQL\*Net, NetBIOS, ESP, DHCP Relay, DNS, GTP, and SIP

## Firewall Attack Detection and Protection

- Generalized Day 0 anomaly-based flood protection with patent-pending Intelligent Cache Management Protections
- SYN flood protection to specifically protect inbound servers, e.g. Web servers, from inbound TCP SYN floods
- Strict TCP validation to ensure TCP session state enforcement, validation of sequence and acknowledgment numbers,
- Rejection of bad TCP flag combinations
- Initial Sequence Number (ISN) rewriting for weak TCP stack implementations
- Fragment flood protection with robust fragment reassembly, ensures no partial or overlapping fragments are transmitted
- Generalized IP packet validation including detection of malformed packets
- DoS mitigations for over 190 DoS attacks, including ping of death, land attack, tear drop attack, etc.
- Drops bad IP options as well as source route options
- Connection rate limits to minimize effects of new attacks.

## QoS/Bandwidth Management

- Classified by physical port, virtual firewall, firewall rule, session bandwidth guarantees – Into and out of virtual firewall, allocated in bits/second
- Bandwidth limits - Into and out of virtual firewall, allocated in bits/second, packets/session, sessions/second
- ToS/DiffServ marking and matching
- Integrated with application layer filters

## Content Security

- HTTP Filter Keyword support integrated with HTTP Application Filter
- Basic content filtering with configurable whitelist/blacklist and content keyword matching.
- URL redirection for blacklist sites
- Rules-based routing feature for HTTP, SMTP and FTP features (Security Management Server v9.1 or later)
  - Interoperates with all 3rd party Anti-virus, Anti-Spam, and Content Filtering systems
  - Redirects only protocol-specific packets to 3rd party systems performing Anti-virus, Anti-spam, and content filtering services.
- Application-layer protocol command recognition and filtering
- Application-layer command line length enforcement
- Unknown protocol command handling
- Extensive session-oriented logging for application-layer commands and replies
- Hostile mobile code blocking (Java®, ActiveX™)

## Firewall User Authentication

- Browser-based authentication allows authentication of any user protocol
- Built-in internal database – user limit 10,000
- Local passwords, RADIUS, SecurID
- User assignable RADIUS attributes
- Certificate authentication

## VPN

- Maximum number of dedicated VPN tunnels – 7,500
- Manual Key, IKEv1, IKEv2, DoD PKI, X.509
- 3DES (168-bit), DES (56-bit)
- AES (128, 192, 256-bit)
- SHA-1 and MD5 authentication/integrity
- Replay attack protection
- Remote access VPN
- Site-to-site VPN
- IPSec NAT Traversal/UDP encapsulated IPSec
- IKEv2 IPSec NAT Traversal and dead peer detection
- LZS compression
- Spliced and nested tunneling
- Fully meshed or hub and spoke site-to-site VPN

## VPN Authentication

- Local passwords, RADIUS, SecurID, X.509 digital certificates
- PKI Certificate requests (PKCS 12)
- Automatic LDAP certificate retrieval
- DoD PKI

## High Availability

- VPN Firewall Brick security appliance to VPN Firewall Brick security appliance active/passive failover with full synchronization
- 400 millisecond device failure detection and activation
- Session protection for firewall, VoIP and VPN
- Link failure detection
- Alarm notification on failover
- Encryption and authentication of session synchronization traffic
- Self-healing synchronization links
- Pre-emption and IP tracking for improved health state checking
- Seamless system upgrade with no downtime for redundant deployments

# TECHNICAL SPECIFICATIONS

## Diagnostic Tools

- Out of band debugging and analysis via serial port/modem/terminal server
- Centralized, secure remote console to any VPN Firewall Brick
- VPN Firewall Brick security appliance supports Ping, Traceroute, and Packet Trace with filters
- Remote Brick security appliance bootstrapping
- Real-time log viewer analysis tool
- Java-based Navigator for remote access to management system

## 3-Tier Management Architecture

- Centralized, carrier-class, active/active management architecture with Alcatel-Lucent Security Management Server (SMS) software
- Secure VPN Firewall Brick to SMS communications with Diffie-Helman and 3DES encryption, SHA-1 authentication and integrity and digital certificates for VPN Firewall Brick security appliance/Alcatel-Lucent Security Management Server authentication
- Up to 100 simultaneous administrators securely managing all aspects of up to 20,000 VPN Firewall Brick units in a hierarchical management cluster.
- Secure, reliable, redundant real-time alarms, logs, reports

## Certifications

- ICSA V4.1 Firewall Certification in process,
- ICSA V1.2 IPSec Certification in process,
- FIPS 140-2 Certification in process
- EAL-4 Certification in process
- NEBS™ Level 3 (compliant to Telecordia GR1089-CORE and GR-63-CORE) in process for Brick 1200 HS DC version.

## Mean Time Between Failure

- Brick 1200 Basic: 129,801 hours
- Brick 1200HS AC: 128,820 hours
- Brick 1200HS DC: 128,833 hours
- Telecordia SR-332 at Standard Reference Conditions.

## Dimensions (W x L x H)

- Est. 19" x 19" x 3.5" (2U)
- Est. 48.3 cm x 48.3 cm x 8.9 cm (2U)
- Rack Mountable per EIA-310 specification
- Est. Weight: 44 lbs (20 kg)
- Est. Shipping Weight: 50 lbs (22 kg)

## Cooling

- Chassis fan (Intake and Exhaust), power supply fans

## Operating Altitude

- Up to 13,123 ft (4,000 m)

## Environmental

### OPERATING

- Normal Operating Temperature: 0 to 40° C
- Shock: 2.5g at 15 – 20 ms on any axis
- Relative humidity: 5–85% at 40 C. (non-condensing)
- Vibration: 5g at 2 – 200Hz on any axis

### NON-OPERATING

- Temperature: -40 to 70° C
- Shock: 35g at 15 – 20 ms on any axis
- Relative humidity: 5–90% at 40 C. (non-condensing)
- Vibration: 5g at 2 – 200Hz on any axis

## Power

### AC MODELS:

- Hot Swappable, Internal Dual AC to DC Power Supply: 500W max
- Auto-ranging: 100 to 240 VAC, 47 to 63 Hz
- Consumption: 8A @ 120 VAC; 5A @ 240 VAC

### DC MODEL:

- Hot Swappable, Internal Dual DC to DC Power Supply: 500W max
- Input Range: -36 to -72 VDC
- Consumption: 10A @ -48 VDC, 8A @ -60VDC

## Alcatel-Lucent Security Management Server

### Software Requirements

- Sun Solaris™ 2.8, 2.9 or 2.10 on SPARC processors
- Microsoft Windows® 2000 Professional, Windows® 2000 Server, Windows XP Professional, Windows Server 2003 or Windows Vista Business.

### SUN® WORKSTATION OR SERVER FOR SUNSOLARIS OPERATING SYSTEM:

- Sun UltraSPARC5 (600 MHz processor or better) or better
- 512MB of system memory (minimum)
- Swap space at least as large as system memory
- 2 GB free disk space in file system partition where software is to be installed
- 50MB free disk space in root partition
- 1 10/100 Ethernet interface
- CD-ROM drive
- 3.5" floppy drive, USB port and serial port.
- Video card capable of supporting 1024x768 resolution (65,535 colors)

### INTEL®-BASED COMPUTER (FOR MICROSOFT WINDOWS® 2000 PROFESSIONAL, WINDOWS 2000 SERVER, WINDOWS XP PROFESSIONAL, WINDOWS SERVER 2003)

- 700 MHz Pentium III processor (minimum)
- 512 MB system memory (minimum), higher recommended
- CD-ROM drive
- Swap space at least as large as install system memory
- 2 GB free space on an NTFS partition
- 3.5" floppy, USB port and serial port.
- 1 Ethernet 10/100 card
- Video card capable of supporting 1024x768 resolution

### INTEL®-BASED COMPUTER (FOR MICROSOFT VISTA® BUSINESS)

- 2.0 GHz processor (minimum)
- 1GB system memory (minimum), 2GB recommended
- CD-ROM drive
- Swap space at least as large as install system memory
- 80 GB harddisk with 40GB free space on a NTFS partition
- 3.5" floppy, USB port and serial port.
- 1 Ethernet 10/100 card
- Video card capable of supporting 1024x768 resolution

	North and South America	Europe	Asia, Pacific
Product Safety Approvals	CSA Certified to UL® 60950-1, 1st Edition	CE	CB Scheme to EN/IEC 60950-1
	CAN/CSA 22.2 No. 60950-1-03	CB Scheme to EN/IEC 60950-1	AS/NZS 3260 1993 with amendments 1,2,3 and 4
			ACA TS 001 1997
EMC Approval	FCC Part 15, Class A	CE	VCCI Class A
	ICES-003, Class A	EN55024/VCC	AS/NZS – CISPR Pub 22, Class A
		EN300-386, Class B	
Network Attachment Approvals	Not Applicable	Not Applicable	Not Applicable

## ORDERING INFORMATION

PART NUMBER	DESCRIPTION
109625772	VPN Firewall Brick 1200 AC Model
109625780	VPN Firewall Brick 1200HS AC Model
109625806	VPN Firewall Brick 1200HS DC Model
300912549	1000BaseT Copper SFP Transceiver
300912979	1000BaseSX MMF SFP Transceiver
300533866	1000BaseLX SMF SFP Transceiver
Contact your Alcatel-Lucent Representative or authorized reseller for details	<p><b>Alcatel-Lucent Security Management Server</b> Brick 1200 and 1200HS security appliances require v9.0 (patch level 276) or later version. Available in several configurations to meet your networking requirements.</p> <p><b>Alcatel-Lucent IPSec Client</b> Available in several configurations to meet your networking requirements.</p>

To learn more, contact your dedicated Alcatel-Lucent representative, authorized reseller, or sales agent. You can also visit our Web site at [www.alcatel-lucent.com](http://www.alcatel-lucent.com).

This document is provided for planning purposes only and does not create, modify, or supplement any warranties, which may be made by Lucent Technologies relating to the products and/or services described herein. The publication of information contained in this document does not imply freedom from patent or other protective rights of Lucent Technologies or other third parties.

Brick is a registered trademark of Alcatel-Lucent. ActiveX is a trademark of Microsoft corporation. Java is a trademark of Sun Microsystems, Inc. NEBS is a trademark of Telcordia Technologies. Pentium® is a registered trademark of Intel Corporation. Solaris is a trademark of Sun Microsystems, Inc. Sun® is a registered trademark of Sun Microsystems, Inc. UL® is a registered trademark of Underwriter's Laboratories. Windows® is a registered trademark of Microsoft.

**[www.alcatel-lucent.com](http://www.alcatel-lucent.com)**

Alcatel, Lucent, Alcatel-Lucent and the Alcatel-Lucent logo are trademarks of Alcatel-Lucent. All other trademarks are the property of their respective owners. Alcatel-Lucent assumes no responsibility for the accuracy of the information presented, which is subject to change without notice.  
© 2007 Alcatel-Lucent. All rights reserved. 031932-00 Rev. D 11/07